


VIEWING DIRECTION

TOL ± 0.2 UNLESS SPECIFIED

PIN 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	COM	NC	AC	B	1bc	1DP	2e	2d	2c	2DP	3e	3d	3c	3DP	4e	4d	4c	M	K
PIN 21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM	F	C	A	V	m	4b	4a	4f	4g	3b	3a	3f	3g	2b	2a	2f	2g	ARROW	MINUS
																			DC

- CHARACTERISTICS:
- 1) OPERATING VOLTAGE : 3.0V
 - 2) OPERATING TEMPERATURE : -20°C TO 70°C
 - 3) STORAGE TEMPERATURE : -25°C TO 85°C
 - 4) DRIVING METHOD : STATIC
 - 5) VIEWING DIRECTION : 6 O'CLOCK
 - 6) DISPLAY TYPE : REFLECTIVE

MECHANICAL TOL. ±0.2 UNLESS SPECIFIED



REVISION NO.	00	REVISION RECORD	DATE
APPROVAL	COUNTER DRAWING	CUSTOMER REFERENCE	15-JAN-96
APPROVED BY			
POSITION			
COMPANY NAME	STANDARD	OUR REF.	C.L.
DATE		SCALE	3 : 1
APPROVAL	DRAFTING	CUSTOMER-SERVICE	ENGINEERING
APPROVED BY			
DATE			
PROJECTION			
DRAWN BY	KURT WAT	UNIT IN	mm
		SHEET	1 OF 1
S5063B			
CLOVER DISPLAY LIMITED			