



CHARACTERISTICS :

- 1) OPERATING VOLTAGE : 3.0V(N TYPE)
5.0V(L TYPE)
5.0V(W TYPE)
- 2) OPERATING TEMPERATURE : 0°C TO 55°C(N TYPE)
-30°C TO 60°C(L TYPE)
-30°C TO 80°C(W TYPE)
- 3) STORAGE TEMPERATURE : -10°C TO 60°C(N TYPE)
-35°C TO 65°C(L TYPE)
-35°C TO 85°C(W TYPE)
- 4) DRIVING METHOD : 1/3DUTY, 1/3BIAS
- 5) VIEWING DIRECTION : 6 O'CLOCK
- 6) DISPLAY TYPE : REFLECTIVE

TOL. ±0.2 UNLESS SPECIFIED.

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
COM1	S4	AC	4B	3F	3A	3B	2F	2A	2B	1F	1A	1B	S3			COM1		
COM2	S5	S6	4C	3E	3G	3C	2E	2G	2C	1E	1G	1C	K	S1	S2		COM2	
COM3		S7	4DP		3D	3DP		2D	2DP		1D		m	V	A			COM3

S5083 S5083P

		DRAWN BY : L.K.W	P/N
		CHECKED BY	OUR REF. S5083
PROJECTION		APPROVED BY	SHEET 1 OF 1
DATE 1-12-1989		SCALE 3 : 1	UNIT mm
CLOVER DISPLAY LIMITED			