



- CHARACTERISTICS :
- 1) OPERATING VOLTAGE : 3.0V (N TYPE)  
5.0V (L TYPE)  
5.0V (W TYPE)
  - 2) OPERATING TEMPERATURE : 0°C TO 55°C (N TYPE)  
-30°C TO 80°C (L TYPE)  
-30°C TO 80°C (W TYPE)
  - 3) STORAGE TEMPERATURE : -10°C TO 60°C (N TYPE)  
-35°C TO 65°C (L TYPE)  
-35°C TO 85°C (W TYPE)
  - 4) DRIVING METHOD : STATIC
  - 5) DISPLAY TYPE : REFLECTIVE
  - 6) VIEWING DIRECTION : 6 O'CLOCK

TOL. ±0.2 UNLESS SPECIFIED

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	Y	Z					P1	1E	1D	1C	P2	2E	2D	2C	P3	3E	3D	3C	3B
21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
3A	3F	3G	2B	2A	2F	2G	COL	1B	1A	1F	1G						10 BAT	X	COM

 PROJECTION		DRAWN BY K.H.LAM	P/N
		CHECKED BY	OUR REF. S5094-KB-NCR
 SCALE 4 : 1		APPROVED BY	SHEET 1 OF 1
 DATE 27-4-90		UNIT mm	
 CLOVER DISPLAY LIMITED			

S5094

DATE 27-4-90

PROJECTION

SCALE 4 : 1

UNIT mm

CLOVER DISPLAY LIMITED