



- CHARACTERISTICS:
- 1) OPERATING VOLTAGE : 3.0V
  - 2) OPERATING TEMPERATURE : 0°C TO 55°C
  - 3) STORAGE TEMPERATURE : -10°C TO 60°C
  - 4) DRIVING METHOD : STATIC
  - 5) VIEWING DIRECTION : 6 O'CLOCK
  - 6) REFLECTIVE

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	COM	NC	NC	4E	4D	4C	4DP	3E	3D	3C	3DP	2E	2D	2C	2DP	1E	1D	1C	1B	1A
COM	1A	1F	1G	2B	2A	2F	2G	2L	3B	3A	3F	3G	NC	4B	4A	4F	4G	NC	NC	COM

REVISION RECORD		REVISED BY	DATE
APPROVAL	COUNTER DRAWING	ENGINEERING SAMPLE	
APPROVED BY	FULL NAME	POSITION	COMPANY NAME
DATE			
DRAWN BY	CHECKED BY	OUR REF.	P/N
APPROVED BY	SHEET 1 OF 1		
SCALE 3 : 1	UNIT mm		

COUNTER DRAWING      DATE

PROJECTION

**CLOVER DISPLAY LIMITED**