


# LM5560-Q45

Intel® Q45 with Core™2 Quad Micro-ATX Motherboard



## Features

- Socket 775 supports Intel® Core™2 Quad FSB 800/ 1066/ 1333MHz CPU
- Intel® Q45 + ICH10DO Chipset supports Intel AMT 5.0 and vPro
- Four 240-pin DDR2 DIMM 667/ 800MHz, up to 8GB
- Intel Graphic Media Accelerator 4500
- Realtek ALC888, 5.1 + 2 Channel with 2 independent HD Streaming Audio
- Intel 82567LM Gigabit LAN
- 1 PCI-E x 16, 1 PCI-E x 1, 2 PCI, 1 IDE
- 2 COM, 12 USB 2.0, 6 SATA II, 16-bit GPIO, 1 LPT
- 6 SATA II support RAID 0, 1, 5, 10 function
- Intel Integrated TPM 1.2

## Specifications

System	
<b>CPU</b>	Intel® LGA775 socket supports Core™2 Quad/ Core™2 Duo/ Celeron® with 45nm process technology
<b>FSB</b>	1333 / 1066 / 800 MHz
<b>BIOS</b>	Award 32Mb SPI BIOS
<b>System Chipset</b>	Intel® Q45 + ICH10DO Chipset
<b>I/O Chip</b>	Winbond W83627DHG-A
<b>System Memory</b>	Four 240-pin DIMM sockets support up to 8GB dual channel DDR2 800/667/533 SDRAM
<b>Watchdog Timer</b>	Reset : 1 to 255 sec/min per step
<b>H/W Status Monitor</b>	Monitoring temperature, voltage, and cooling fan status. Auto throttling control when CPU overheats
<b>Expansion</b>	1 PCI-E x 16, 1 PCI-E x 1, 2 PCI (PCI Rev. 2.3 compliant)
<b>Power State</b>	S1, S3
<b>TPM</b>	Intel® Integrated TPM1.2
<b>Wake up on LAN or Ring</b>	LAN (PXE)
<b>SmartFan Control</b>	Supports 3 modes (Silent/ Optimal/ Performance)


I/O	
<b>MIO</b>	1 IDE, 6 SATA II, 2 COM RS-232 (5V/12V), 1 LPT, 1 PS/2 Keyboard, 1 PS/2 Mouse
<b>USB</b>	12 USB 2.0
<b>GPIO</b>	PCA9555 supports 16-bit General Purpose I/O for 8-bit DI and 8-bit DO

Display	
<b>Chipset</b>	Intel Q45 integrated Graphic Media Accelerator 4500
<b>Display Memory</b>	Intel DVMT 4.0 supports up to 352 MB video memory
<b>Max. Resolution</b>	2048 x 1536 (@75Hz)
<b>VGA</b>	On board
<b>LVDS</b>	Through ADD2 LVDS Card
<b>DVI</b>	Through ADD2 DVI Card
<b>HDMI</b>	Through ADD2 HDMI Card
<b>2<sup>nd</sup> VGA</b>	Through ADD2 VGA Card

Audio	
<b>Audio Codec</b>	Realtek ALC888, 5.1 + 2 CH HD Audio
<b>Audio Interface</b>	Line-in, Line-out, Mic-in, S/PDIF Out

Ethernet	
<b>LAN</b>	Intel 82567LM Gigabit LAN

## Block Diagram



LM5560-Q45

### Back Panel I/O Port

- 1 PS/2 Keyboard
- 1 PS/2 Mouse
- 1 VGA Port
- 1 LPT Port
- 1 COM RS-232 Port
- 1 LAN RJ45 Port
- 4 USB Ports
- Audio I/O (3 jacks)

### Internal I/O Connector

- 4 USB Connectors support 8 USB Ports
- 1 IDE Connector
- 6 SATA Connectors
- 1 CPU Fan Connector
- 1 Chassis Fan Connector
- 1 Power Fan Connector
- 1 Front Panel Header
- 1 S/PDIF Out Header
- 1 Chassis Intrusion Header
- 1 4-pin Audio Amplifier

### Mechanical & Environmental

<b>Power Requirement</b>	+12V 10.94A	+5V 4.22A	+3.3V 1.74A	5VSB 1.67A
<b>Power Type</b>	ATX			
<b>Power Connector</b>	1 24-pin ATX Power Connector 1 4-pin ATX 12V Power Connector			
<b>Operating Temperature</b>	0 to 60°C (32 to 140°F)			
<b>Operating Humidity</b>	0% to 90% relative humidity, non-condensing			
<b>Size (L x W)</b>	9.6" x 9.6" (243.84 mm x 243.84 mm)			
<b>Weight</b>	1.35 lbs (0.6 Kg)			

\*\* The product information and specifications are subject to change without prior notice.  
 \*\* All the rights of above logos and trademarks belong to their representative owners.