

52X CD-ROM: CDU5225



52x max. CD-ROM drive (with Turbo Boost)

internal 12/8cm CD-ROM disc drive

(half height form factor)

IDE/ATAPI interface with UltraDMA 33

(max. 33 MByte/sec transfer rate)

Tray load mechanism supporting horizontal and vertical use

Dust protected enclosure



Specifications	52X CD Reader (CDU5225)
Data Transfer Rate	3000-7800 kByte/s *
Access Time	85 ms
Cache Memory	96 kByte
Mechanism	motorized Tray load mechanism for horizontal and vertical use
Interface	IDE / ATAPI
Burst Transfer Rate	PIO mode 4 / Ultra-DMA 33
Audio	line-out (MPC compatible) at the back
Compatibility	High Sierra, ISO9660, CD-Audio, CD-ROM (mode1 and mode 2), CD-ROM XA, Single- and MultiSession Kodak Photo CD, CD-I (FMV), Video CD, Enhanced Music CD (CD+), MPC Level 3, CD TEXT, CD-RW read (in compliance with MultiRead spec.), PC2001
Available colours	beige, black, silver
Weight	0.7kg
Dimensions	148.2mm x 42mm x 170mm

*) Turbo boost active. Default CD speed is max. 40x (6000 kByte/s)