

16/52X Combo: CRX320EE



16x max. read speed for DVD-ROM

52x max. read speed for CD (with Turbo Boost)

52x max. write speed for CD-R

32x max. write speed for CD-RW

IDE/ATAPI interface with UltraDMA 33

(max. 33 MByte/sec transfer rate)

Buffer under run error prevention

Emergency eject



Specifications	Combo (CRX320EE)			
	DVD-ROM	CD-ROM	CD-R	CD-RW
Transfer Rate read	16x CAV (max. 21600 kByte/s)	52x CAV *	52x CAV *	40x CAV
Transfer Rate write	J.	J.	52x CAV (max. 7900 kByte/s)	32x PCAV (max. 4800 kByte/s)
Access Time	105 ms	105 ms		
Mechanism	motorized Tray load mechanism for horizontal and vertical use			
Interface	IDE / ATAPI			
Burst Transfer Rate	PIO mode 4 / Ultra DMA 33			
Cache Memory	1.5 MByte			
Audio	line-out at the back (MPC compatible)			
Media/Modes supported	DVD read, CD-ROM, CD-ROM XA, CD-Audio, CD Extra, CD Text, CD-I, CD-I Ready, CD-Bridge, Photo-CD, Video CD, Hybrid CD			
Writing methods	DAO (disc at once), SAO (session at once), TAO (track at once) with zero gap, variable or fixed packet, multisession			
Compatibility	MPC Level 3, MultiRead, PC2001			
Weight	0.9 kg			
Dimensions	148.2mm x 42mm x 170mm			

